



PR MYSLOVÉ VENTILÁTORY



Pro střední velké prostory - restaurace, sklady, garáže a podobně

TT

- 0RWRU V NXOLĪNRY ě PLĚR@L VNU
- U\FKORVWQ`YHQWLOĚWRU
- 1DSĚMHQ` 9 +]
- 0D[SURYR]Q`WHSORWD r&
- .U\W` ,3;

Prmyslové axiální ventilátory



Obrázek	2EM	Typ (Ø V « ULH	3`NRQ PLQ PD[3U1WRN Y]G\X PLQ PD[FK+OXF PLQ PD[QRVW PLQ PD[P%G%\$ NV
	TOP009541	TT 100	21 33	145 187	27 36	8	
	1009557	TT 100 T	21 33	145 187	27 36	8	
	TOP009543	TT 125	23 37	220 280	28 37	8	
	1009558	TT 125 T	23 37	220 280	28 37	8	
	1009546	TT 125 S	28 54	240 320	31 42	8	
	1009289	TT 125 ST	28 54	240 320	31 42	8	
	TOP009548	TT 150	30 60	405 520	33 44	4	
	1009549	TT 150 T	30 60	405 520	33 44	4	
	1009553	TT 160	30 60	405 520	33 44	4	
	1009559	TT 160 T	30 60	405 520	33 44	4	


TT PRO

- 0RWRU V NXOLĪNRY ě PLĚR@L VNU
- U\FKORVWQ`YHQWLOĚWRU
- 1DSĚMHQ` 9 +]
- 9ěNRQQŸM#`RSURWL
- NODVLFN«PX YHQWLOĚWRU X 77
- 0D[SURYR]Q`WHSORWD r&
- .U\W` ,3;
- 3`NODG SRX@LW`

Prmyslové axiální ventilátory



do potrubí, IPX4

Obrázek	2EM	Typ (Ø V « ULH	3`NRQ PLQ PD[3U1WRN Y]G\X PLQ PD[FK+OXF PLQ PD[QRVW PLQ PD[P%G%\$ NV
	TOP0095410	TT PRO 100	23 25	180 245	27 32	8	
	1095411	TT PRO 100 T	23 25	180 245	27 32	8	
	1095430	TT PRO 125	25 29	240 350	29 34	8	
	1095431	TT PRO 125 T	25 29	240 350	29 34	8	
	TOP0095480	TT PRO 150	42 50	415 565	37 46	4	
	1095481	TT PRO 150 T	42 50	415 565	37 46	4	
	1095530	TT PRO 160	42 50	415 565	37 46	4	
	1095531	TT PRO 160 T	42 50	415 565	37 46	4	
	TOP0095501	TT PRO 200	76 108	830 1040	45 52	4	
	1095502	TT PRO 200 T	76 108	830 1040	45 52	4	
	1095532	TT PRO 250	125 177	1110 1400	47 55	2	
	1095533	TT PRO 315	230 320	1570 2050	49 58	2	

TECHNICKÉ PARAMETRY:

.RPSOHWQ`WHFKQLFNRX VSHFLĎNDFL
UR]PŸURYě YěNUHV VFK«PD]DSRMHQ`
D GDO#`LQIRUPDFH QDOH]QHWH QD

www.eshop.eleman.cz