



Valena Life™ Finish plates Black/Graphite


Cat. No(s): 7 542 51/52/53/54/55/61
7 542 71/72/73/74/75



7 542 51



7 542 52









7 542 53


1. USE

Frame plates for fitting on Valena mechanisms 1 to 5 gangs.

2. RANGE

PLATES SUPPLIED WITH SMOKE UNDER-PLATES		Black	Graphite
	1-gang	7 542 51	7 542 71
	2-gang	7 542 52	7 542 72
	3-gang	7 542 53	7 542 73
	4-gang	7 542 54	7 542 74
	5-gang	7 542 55	7 542 75
SPECIFIC PLATES FOR DOUBLE SOCKET OUTLETS (2 x 2P+E) SUPPLIED WITH SMOKE UNDER PLATE			
	Plate 1-gang for double socket outlet	7 542 61	-

3. OVERALL DIMENSIONS (mm)



Cat. Nos.	A	B	C
7 542 51/71	86	86	9.8
7 542 52/72	86	157	9.8
7 540 53/73	86	288	9.8
7 540 54/74	86	299	9.8
7 540 55/75	86	370	9.8
7 542 61	114	86	14

4. MOUNTING

The plates are clipped via notches to supports (the notches are used to compensate for the thickness. Example: wall carpet). Easy to remove with a screwdriver using the slots on the side of the plate.

5. TECHNICAL DATA

■ 5.1 Mechanical characteristics

Impact tests: IK 04

■ 5.2 Material characteristics

Decor plates: ABS

Under-plates: PC

UV-resistant

Halogen-free

Self-extinguishing: 650° C/30 s

■ 5.3 Climate characteristics

Storage temperature: - 10°C to + 70°C

Use temperature: - 5°C to + 50°C

6. CLEANING

Surface cleaning with a cloth.
Do not use: acetone, tar remover, trichloroethylene.
Dish-washer proof.

■ 6.1 Resistance to the cleaning products

- Hexane (EN 60669-1),
- Methylated spirit,
- Soapy water,
- Diluted ammonia,
- Pure bleach diluted to 10%,
- Window-cleaning product,
- Pre-impregnated wipes.

■ 6.2 Resistance to hospital-grade cleaning products

- Anios,
- Surfanios,
- Bactylisine,
- Diluted hydrogen peroxide (35%).

Caution: Always test before using other special cleaning products.

7. SPECIAL USE

The plates must not be painted.